



US006373507B1

(12) **United States Patent**  
Camara et al.

(10) **Patent No.:** US 6,373,507 B1  
(45) **Date of Patent:** Apr. 16, 2002

(54) **COMPUTER-IMPLEMENTED IMAGE ACQUISITION SYSTEM**

(75) **Inventors:** Franc J. Camara, Redmond; Richard S. Turner, Jr., Woodinville; Mark R. Enstrom, Redmond; Reed K. Bement, Kirkland; Andrew S. Ivory, Woodinville, all of WA (US)

(73) **Assignee:** Microsoft Corporation, Redmond, WA (US)

(\*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** 09/153,432

(22) **Filed:** Sep. 14, 1998

(51) **Int. Cl.<sup>7</sup>** ..... G06F 3/00; G04N 1/32

(52) **U.S. Cl.** ..... 345/825; 345/779; 345/810; 345/902; 358/401

(58) **Field of Search** ..... 345/302, 327, 345/339, 348, 352, 356, 902, 970, 716, 764, 778, 779, 810, 828, 835, 841, 846, 853, 854, 855, 825; 348/231; 358/403, 442, 468, 474, 906, 909.1; 382/312; 707/500.1

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,837,635 A	*	6/1989	Santos	.....	358/401
5,191,645 A	*	3/1993	Carlucci et al.	.....	345/328
5,385,475 A	*	1/1995	Sudman et al.	.....	345/302 X
5,412,773 A	*	5/1995	Carlucci et al.	.....	345/327
5,706,457 A	*	1/1998	Dwyer et al.	.....	345/348 X
5,796,945 A	*	8/1998	Tarabella	.....	345/327 X
5,949,411 A	*	9/1999	Doerr et al.	.....	345/327
6,028,604 A	*	2/2000	Matthews, III et al.	.....	345/352
6,097,389 A	*	8/2000	Morris et al.	.....	345/348 X
6,118,546 A	*	9/2000	Sanchez et al.	.....	358/442 X

**OTHER PUBLICATIONS**

"Host System and Attached Non-Programmable Terminal with Open Parallel Port," IBM Technical Disclosure Bulletin, vol. 38 No. 09 p. 475-478, Sep. 1995.\*  
Microsoft Media Manager Overview.

\* cited by examiner

*Primary Examiner*—Raymond J. Bayerl


*Assistant Examiner*—X. L. Bautista


(74) *Attorney, Agent, or Firm*—Lee & Hayes, PLLC


(57) **ABSTRACT**


An image acquisition system has a computer and one or more imaging devices coupled to the computer. Each imaging device has a device memory and is capable of capturing a digital image and storing the image in its memory. An image device manager is implemented in software on the computer to control operation of the imaging devices. The image device manager presents a user interface (UI) within the familiar graphical windowing environment. The UI has a context space that pertains to a particular imaging context (e.g., scanning, photography, and video). The UI also has a persistently-visible imaging menu positioned within the context space that lists options particular to the imaging context. For example, if the context space pertains to the digital camera context, the menu lists options to take a picture, store the image on the computer, send the image in an email, and so on. In the scanner context, the menu lists options to select an image type, preview an image, send the image to a particular destination, and scan the image. The image acquisition system also includes a set of application program interfaces (APIs) that expose image management functionality to applications. The APIs enable applications to manage loading and unloading of imaging devices, monitor device events, query device information properties, create device objects, capture images using the devices, and store or manipulate the images after their capture.


**45 Claims, 7 Drawing Sheets**





*Fig. 1*


*Fig. 2*

*Fig. 3*

*Fig. 4*

*Fig. 5*

*Fig. 6*

*Fig. 7*



1

# COMPUTER-IMPLEMENTED IMAGE ACQUISITION SYSTEM

## TECHNICAL FIELD

This invention relates to computer-implemented systems for managing imaging devices, such as digital cameras, scanners, and the like. This invention also relates to graphical window user interfaces, and particularly to user interfaces used to facilitate capture and storage management of digital images. This invention further relates to operating systems and browsers that incorporate image device managers and user interfaces.

## BACKGROUND

Digital imaging devices, such as scanners, cameras, video cameras, have been experiencing rapid growth in popularity as their price tags continue to decrease. Recreational photographers enjoy capturing pictures and videos and placing the digital files onto their computers for printing or emailing to friends and relatives. Businesses use scanners to digitally record documents used in day-to-day operation for archival purposes.

Other solutions to this problem already exist. For example, TWAIN and ISIS are two image acquisition systems that are available today. However, both of these solutions have problems. TWAIN lacks robustness and interoperability. ISIS is a proprietary design that renders it difficult to use with other applications.

Accordingly, a task set before the inventor was to create an image acquisition system that was based on an open architecture model and could be integrated with existing applications and operating systems to provide a convenient environment for the user.

## SUMMARY

This invention concerns an image acquisition system that offers an open architecture to integration with existing operating systems and other applications.

In an exemplary implementation, the image acquisition system is implemented on computer, such as a desktop personal computer, having a processing unit, memory, and operating system. One or more imaging devices are coupled to the computer. Examples of the imaging devices include a scanner, a digital camera, a digital video camera, and so forth. Some imaging devices, such as digital cameras, have a device memory and are capable of capturing a digital image and storing the image on its memory. Other imaging devices, such as scanners, may not have their own device memory.

The image acquisition system further includes an image device manager that is implemented in software on the computer to control operation of the imaging devices. The image acquisition system presents a user interface (UI) within the familiar graphical windowing environment. The UI presents a graphical window having a context space that pertains to a particular imaging context (e.g., scanning, photography, and video). In the camera context, the context space presents image files stored on the camera memory and/or on the computer memory. In the scanner context, the context space includes a preview scan area that reveals a preview of the image in the scanner. In the video context, the context space presents video clips stored on the computer memory, but logically represented as belonging to the video camera.

The UI also has a persistently visible imaging menu positioned within the context space that lists options par-

2

ticular to an imaging context. For example, if the context space pertains to the camera context, the menu lists options to take a picture, store a captured image on the computer, send the image in an email, and on. In the scanner context, the menu lists options to select an image type, preview an image, send the image to a particular destination, and scan the image.

The image acquisition system also includes a set of application program interfaces (APIs) that expose image management functionality to applications. The APIs enable applications to manage loading and unloading of imaging devices, monitor device events, query device information properties, create device objects, capture images using the devices, and store or manipulate the images after their capture.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of an image acquisition system.

FIG. 2 is a block diagram of a software architecture for the image acquisition system.

FIG. 3 is a diagrammatic illustration of a graphical user interface window showing integration of the image acquisition system within a familiar file system setting.

FIG. 4 is a diagrammatic illustration of a graphical user interface window showing an opening window for managing imaging devices.

FIG. 5 is a diagrammatic illustration of a graphical user interface window for interfacing with a scanner.

FIG. 6 is a diagrammatic illustration of a graphical user interface window for interfacing with a digital camera.

FIG. 7 is a diagrammatic illustration of a graphical user interface window for interfacing with a digital video camera.

## DETAILED DESCRIPTION

This invention concerns a computer-implemented image acquisition system that manages imaging devices (such as digital cameras, scanners, digital video cameras, and the like) and the images captured by them. In a preferred implementation, the image acquisition system is implemented in a general-purpose computer (e.g., personal computer, laptop, etc.) to manage imaging devices attached locally to the computer or coupled remotely via a network. The image acquisition system supports a graphical user interface windowing environment that integrates image device management with the same look and feel of familiar browsing user interfaces for conventional file systems. In this manner, a user encounters a familiar experience when managing the imaging devices and image files from his/her computer.

### Exemplary System Architecture

FIG. 1 shows an image acquisition system 20 having a computer 22 coupled to multiple imaging devices 24-30. The computer 22 is a general-purpose computing device that is described and illustrated, for discussion purposes, as a desktop personal computer (PC). The computer 22 has a processing unit 40, a volatile memory 42 (e.g., RAM), a non-volatile data memory 44 (e.g., disk drive, etc.), a non-volatile program memory 94 (e.g., ROM, disk drive, CD-ROM, etc.), a display 48 (e.g., VGA monitor), and a universal serial bus (USB) 50. An operating system/browser 52 is stored in program memory 46 and executed on the processing unit 40 when the computer is booted. Examples of suitable operating systems 52 include the Windows-brand operating systems from Microsoft Corporation and the operating systems from Apple Computer. Although a USB 50 is

shown and described, other bus architectures may be used, including general serial buses, a SCSI bus, an IEEE 1394 serial bus that conforms to the IEEE 1394 specification, and so forth.

The imaging devices 24–30 are coupled to the computer via a serial connection to the USB 50. Illustrated examples of the imaging devices include a scanner 24, a video camera 26, and a digital camera 28. However, other imaging devices (e.g., copiers, facsimile machines, etc.) may also be used in conjunction with aspects of this invention, as represented by the generic imaging device 30. Some of the imaging devices have their own memory, as represented by memory 32 in imaging device 30. For example, the digital camera may have its own memory, whereas the scanner typically does not have a memory.

The image acquisition system 20 includes an image device manager 60, which is implemented as a software component loaded on the computer 22. More particularly, the image device manager 60 is stored in program memory 46 and runs on processing unit 40 during execution. The image device manager 60 may be integrated into the operating system 52 (as shown), executed as a set of services, or implemented as a separate self-contained program.

The image acquisition system 20 also has a user interface 62, which is preferably a graphical user interface that presents a graphical window having a context space pertaining to the imaging context. Depending upon the particular context, the context space may list available imaging devices for which device drivers have been loaded onto the computer, or list digital image files captured by one or more of the imaging devices, or show an image being scanned in by the scanner.

The user interface 62 further presents a persistently visible imaging menu positioned within the context space. The imaging menu lists options that are particular to controlling the various imaging devices. For instance, when the context space pertains to the camera context, the menu lists a “Take Picture” option that is specific to operating the digital camera 28. Upon user selection of “Take Picture”, the image device manager 60 directs the digital camera 28 to record the current image obtained through the camera lens. In the scanner context, the menu lists a “Scan/Open” option that is particular to operating the scanner. Upon selection of this option, the image device manager 60 directs the scanner to scan the current image.

The image device manager 60 has an image device driver 64 and a set of APIs (application program interfaces) 66. The image device driver 64 controls operation of the imaging device in response to selected options in the context-specific menu. The driver 64 is the code that facilitates communication with the imaging device over the USB 50 and passes commands to capture an image, to read image files from the device’s local memory, to obtain the device’s properties, and so forth.

The APIs 66 define a set of interfaces that can be used to access the functionality of the image device manager 60. These APIs are described below in a section entitled “Image Acquisition API”.

#### Exemplary Software Architecture

FIG. 2 shows a software architecture 70 for implementing the image acquisition system. At the kernel level, the architecture 70 includes kernel I/O drivers that include a bus driver to drive serial communication with the imaging device over the USB 50.

At the user level, a device driver 74 is loaded for the particular imaging device connected to the computer. The

device driver 74 includes a device object, an optional UT, and optional image processing capabilities. An image device manager object 76 is called to initialize and select an image device, and create the device interface. The image device manager object 76 performs such tasks as instantiating a device driver object 74, determining the device status, monitoring events from the device, and so forth.

A COM (component object model) layer 78 exposes the device driver object 74 and image device manager object 76 to an upper level application 80. The application layer 80 represents both traditional TWAIN based applications that utilize a TWAIN compatibility layer 82, as well as new applications that support the APIs 66. Unlike the traditional TWAIN model, however, the TWAIN compatibility layer 82 interacts with the COM-based objects 74 and 76 rather than TWAIN-based devices.

#### Image Acquisition User Interface

The image acquisition system may be incorporated into the operating system, exist as a set of services, or be run as a separate, self-contained application. For discussion purposes, the image acquisition system is described as being integrated into an operating system that supports a graphical user interface windowing environment.

FIG. 3 shows an initial graphical user interface window 100 presented on the computer display 48. This window 100 is illustrated as the familiar “My Computer” screen within a browser-based windowing setting, which is well known to users of Windows-brand operating systems. The “My Computer” window 100 presents a context for listing the major components that make up the user’s PC, including disk drives, printers, a control panel, and networking functionality.

Of interest to the image acquisition system is the integration and treatment of the imaging devices as a folder 102 organized with the other general computer components. This provides a convenient starting point for the user to access the imaging devices 24–30 that are coupled to the computer 22.

When the user activates the “Imaging Devices” folder icon 102 for the first time, an installation Wizard comes up to guide the user through the installation of an imaging device. Suppose, for example, the user has installed two scanning devices and a digital camera. Activating the “Imaging Devices” icon 102 navigates to a new “Imaging Devices” window.

FIG. 4 shows the “Imaging Devices” window 110 presented on the computer display 48. The “Imaging Devices” window 110 pertains to an imaging context and lists the imaging devices that have been installed on the computer. In this example, the window lists an “add imaging device” icon 112 and icons for the three installed devices: a “My Scanner” icon 114 for a locally installed scanner, a “My Camera” icon 116 for the installed camera, and a “Jake’s Scanner” icon 118 for remotely installed (via a network connection) scanner. Activation of the “add imaging device” icon 112 recalls the wizard to enable the user to install any additional imaging devices.

The “Imaging Devices” window 110 distinguishes between devices that are currently available and those that are not available (e.g., offline, physically removed, etc.). Devices that are not available are dimmed and the user has the option of uninstalling them. In FIG. 4, the second scanner identified as “Jake’s Scanner” is not available and hence the icon 118 is dimmed.

Activating one of the imaging devices listed in window 110 causes the image acquisition system to present different windows exhibiting contexts that are specific to the selected

5

imaging device. Within these device-oriented windows, the image acquisition system presents context-specific menus that contain items or options pertinent and relevant to the particular imaging device.

FIG. 5 shows a "My Scanner" window 120 that is presented upon selection of the "My Scanner" icon 114 in FIG. 4. The scanner window 120 presents a context space 122 that pertains to the scanning context. The context space 122 has a preview scan space 124 and a persistently-visible, context-specific menu 126 positioned adjacent the preview scan space within the graphical window 120.

The context-specific menu 126 is always visible in the scanner window 120. The menu 126 offers options that are tailored to operating the scanner attached to the computer or remotely coupled to the computer via a network. While some of the options may be included in a context menu (i.e., a menu that appears near the pointer following a right mouse click), the persistently-visible menu 126 lists operating specific options tailored to the scanner that are not included elsewhere in the user interface.

The menu 126 includes an image type selection 128 that has a pull-down list of various image types from which a user may select. A non-exhaustive list of image types includes color photograph, black and white photograph, color line art, black and white line art, and text. The image types included in the pull-down list 128 are specific to the device. Some imaging devices may not provide support for a given format and hence the format is omitted in that particular list.

A destination selection 130 has a pull-down list of various choices on what to do with the scanned image. For instance, the list 130 might include using the image in an application, faxing the image, printing the image, copying the image to a clipboard, and saving the image in a file. The destination selection simplifies the output operation for the user. For example, selection of a choice directly affects the acquisition parameters and image quality without requiring the user to know what parameters to set.

The persistently-visible context-specific menu 126 also has a "New Preview" command 132 that directs scanners to create a preview image of an image that is currently in the scanning bed. The image is presented in the preview scan space 124. When the image appears in the scan space 124, a preview control 134 is provided to allow the user to select a region of the image for a final scan. In the illustrated implementation, the control 134 is shown as a dashed rectangular box framing the picture. The user can manipulate the box 134 to capture all or less than all of the image. Upon selection of the region, the control can proportionally resize the image to reflect the size of the scanner bed and automatically configure the scanner to make the appropriate adjustments to capture the selected image portion.

The menu 126 includes a "Scan/Open" command 136 to direct the scanner to capture the image. When this command is selected, the scanner scans the image in its bed. Concurrently with this scanning action, the image progressively appears in the preview scan space 124 to visually convey that the scanner is scanning the image. In one implementation, the image is progressively displayed row-by-row from top to bottom of the image.

The menu 126 includes a "Save" option 138, which directs the scanner to capture the image as a file and store the file in the computer memory. The last listed option is a "Send to" option 140, which allows the user to send the image to various locations (or applications) on the PC, such as for packaging in a facsimile or email.

6

FIG. 6 shows a "My Camera" window 150 that is presented upon selection of the "My Camera" icon 116 in FIG. 4. The camera window 150 presents a context space 152 that pertains to the camera context. The context space 152 has a file space 154 and a persistently-visible, context-specific menu 156 positioned adjacent the file space within the graphical window 150.

The context-specific menu 156 is always visible in the camera window 150 and offers options that are tailored to operating the digital camera 28 attached to the computer. While some of the options may be included in a context menu (i.e., a menu that appears near the pointer following a right mouse click), the persistently-visible menu 156 lists operating specific options tailored to the camera that are not included elsewhere in the user interface.

The menu 156 is illustrated as having two tabs: a pictures tab 158 and a camera tab 160. Table 1 contains the options and corresponding functions available on the pictures tab 158.

TABLE 1

Option	Function
Open	Opens a picture with a default registered application
Save in "My Pictures" folder	Downloads the images from the camera and copies them to "My Pictures" directory on computer memory.
Zoom	Changes the window view and allow the user to select one picture at the time and zoom in/out of the picture once it's copied locally.
Send to	Allows the user to send the picture to various locations (or applications) on the PC. For example, the user may choose to "send" the picture to an "email recipient"
Lock on Camera	Allow the user to lock a picture to prevent accidental deletion
Delete from Camera	Allows the user to permanently remove the picture from the camera after a confirmation
Rotate to the Right	Allows the user to rotate the picture 90 degrees to the right.
Rotate to the Left	Allows the user to view properties associated with the selected picture(s).

Table 2 contains the options and corresponding functions available on the

TABLE 2

Option	Function
Take Picture	Triggers the camera to take a picture.
Copy all Pictures	Copies all the pictures to designated location on the PC.
Remove all Pictures	Deletes all pictures in the camera.
Share	Brings up a wizard for the local user to share the camera.
Initialize Memory Card	Enables user to initialize the storage card in the camera.
View Properties	Allows the user to view a summary of the camera properties.

The file space 154 lists files and/or folders that pertain to digital images taken by the digital camera. The files are the images themselves (e.g., JPG files) and the folders contain image files and/or other folders with image files in them.

The file space 154 presents the files that are currently stored on the camera. In this manner, the user can easily view the camera memory as if it were another memory of the

computer. The UI allows easy integration of the camera control into the familiar windowing environment.

To add a picture to the file space, the user captures a picture using the "Take Picture" command in the camera menu 160. The picture then appears as a file in the file space 154. The user can then select the image file by clicking on the file and manipulating the picture using the commands on the pictures menu 158, such as "Rotate to the Left", "Rotate to the Right", "Zoom", and "Send to". The user can also save the image file to the computer memory using the command "Save in My Pictures folder".

FIG. 7 shows a modified "My Camera" window 170 that supports dual-mode cameras (i.e., video and still). The modified window 170 is presented upon selection of the "My Camera" icon 116 in FIG. 4 and is similar to the window 150 of FIG. 6 in that it has a context space 172 with a file space 174 and a persistently-, visible, context-specific menu 176. However, in this modified implementation, the context-specific menu 176 also has a video tab 178 to list options pertaining to operation of the video camera 26.

Notice also that one of the files in the file space 174 is a play-in-place video file 180. This play-in-place video file 180 can be actuated to play a video clip or stream within the small area depicted as box 180. That is, the static video icon in box 180 is replaced with a streaming video at the same location in the file space. Play-in-place video files 180 were first introduced in Media Manager, a multimedia application available from Microsoft.

Table 3 contains the options and corresponding functions available on the video tab 178.

TABLE 3

Option	Function
Play	Plays back a video stream from the video camera.
Open	Opens a video file with a default application
Capture Frame	Directs the video camera to record a single still-image frame.
Capture Video	Directs the video camera to record a video clip.
View Properties	Allows the user to view a summary of the video camera properties.

Other commands may be added to the menu. For instance, a "4stop" command may be employed to halt the capture of live video.

#### Image Acquisition API

The image acquisition API 66 enables applications to manage loading and unloading of all imaging devices, monitor device events, query device information properties, create device objects, capture images using the devices, and store or manipulate the images after their capture. The interfaces are accessible by high level languages (e.g., Visual Basic) as well as lower level ones (e.g., C, C++, etc.). COM is a suitable interface. In this context, each device is exposed as a COM object, whereby the object provides a number of methods and properties associated with the imaging device. As one exemplary implementation, there are three general objects: a device manager object, a camera object, and a scanner object. The objects are described generally below. A more detailed description of the objects and methods are provided at the end of this section.

The device object contains device context and status information for a physical device. Once a device object is

created for a physical device, the physical device controls what device properties are available and what values the properties may assume. There may be multiple device objects created for any physical device. However, a device object has exclusive access to a physical device before any operation (i.e., scan, take a picture, etc.) is performed. Exclusive access to a physical device is made available through a locking/unlocking mechanism.

The device manager is implemented as three objects that perform the following functions:

CIImageInDevMgr object is used to:

Create a device enumerator object

Create a device object when given a DeviceID

Display UI to let a user choose a device object

Display UI to both choose a device and acquire an image from the chosen device.

A CEnumImageInDevInfo object is used to:

Enumerate all ImageIn devices on a system. For each device enumerated, a CIImageInDevInfo object is returned.

A CIImageInDevInfo object is used to:

Query device information properties from the ImageIn device. One of the properties, Device ID, can be used by CIImageInDevMgr to create a device object.

The camera object may expose the following functions:

Open and close the device for communication

Control the device

Update and read device properties

Update and read picture properties

Download, remove, and upload pictures to device

The scanner object may expose the following functions:

Open and close the device for communication

Control the device

Update and read device properties

Set operation intent

ImageIn Device Manager

The ImageIn device manager provides interfaces for enumerating devices, querying properties of installed ImageIn devices and creating ImageIn device objects. The device manager has three objects.

CIImageInDevMgr is used to:

Create an enumerator object, CEnumImageInDevInfo

Create a device object when given a DeviceID.

Display UI to let a user choose a device object.

Display UI to both choose a device and acquire an image from the chosen device.

CEnumImageInDevInfo is used to:

Enumerate all ImageIn devices on a system. For each device enumerated, a CIImageInDevInfo object is returned.

CIImageInDevInfo is used to:

Query device information properties from the ImageIn device. One of the properties, Device ID, can be used by CIImageInDevMgr to create a device object.

Device information properties are distinct from normal device properties in that they are read from the registry and can be queried without forcing the device object to be created.

A program using its own methods to select an ImageIn device would do the following:

Create a CIImageInDevMgr object

Use the IImageInDevMgr interface to create a CEnumImageInDevInfo object

Use IEnumIMAGEIN\_DEV\_INFO interface to create a CImageInDevInfo object for each ImageIn device enumerated.

Use IPropertyStorage interface of CImageInDevInfo object to inspect the device information properties of each device, save the Device ID property from the desired device.

Use the DeviceID property in IImageInDevMgr interface to create an ImageIn device object.

IImageInDevMgr Interface  
EnumImageInDevInfo

---

```
HRESULT IImageInDevMgr::EnumImageInDevInfo (
    LONG          1Flags,
    IEnumIMAGEIN_DEV_INFO** ppIEnum);
```

---

EnumImageInDevInfo creates a standard enumerator for CImageInDevInfo objects. The enumerator itself is a CEnumImageInDevInfo object that has a single interface IEnumIMAGEIN\_DEV\_INFO. Applications can use this API to obtain device information properties from available ImageIn devices.

Parameters:

---

1Flags	Specifies the type of device to enumerate.
ppIEnum	Enumeration interface for CEnumImageInDevInfo objects.

---

GetImageInDevInfo

---

```
HRESULT IImageInDevMgr::GetImageInDevInfo (
    BSTR          bstrDeviceID,
    IPropertyStorage** ppIPropSig);
```

---

Given a device ID GetImageInDevInfo returns an IPropertyStorage interface to CImageInDevInfo objects. This API gives applications a quick way to retrieve device information properties from a stored device ID.

Parameters:

---

bstrDeviceID,	Device ID string returned from device info object.
ppIPropSig	IPropertyStorage interface to CImageInDevInfo objects.

---

CreateImageInDev

---

```
HRESULT IImageInDevMgr::CreateImageInDev(
    BSTR          bstrDeviceID,
    IUnknown**    ppDevice);
```

---

CreateImageInDev creates a device object identified by bstrDeviceID and returns an IUnknown interface to the object. The application can use QueryInterface on this IUnknown to access the other interfaces on a device.

Parameters:

---

bstrDeviceID	Device ID string returned from device info object.
ppDevice	IUnknown interface pointer returned.

---

SelectImageInDev

---

```
HRESULT IImageInDevMgr::SelectImageInDev(
    LONG          1Flags,
    IUnknown**    ppDevice);
```

---

SelectImageInDev displays UI for the selection of ImageIn devices. When the user selects a device, the device object is created and an IUnknown interface is returned. The application can then use QueryInterface on this IUnknown to access the other interfaces on a device. Returns S\_FALSE if the user cancels the selection dialog without making a device selection, S\_OK if the user makes a device selection or an error value if the method fails.

Parameters:

---

1Flags	Operation flags
ppDevice	IUnknown interface pointer returned

---

30 GetImage

---

```
HRESULT IImageInDevMgr::GetImage(
    LONG          1Flags,
    LONG          1Intent,
    LONG          cfFormat,
    STGMEDIUM*    pMedium);
```

---

GetImage displays device selection UI allowing a user to select a device. If the user selects a device, a device is created and device UI is displayed to capture the image. Image data is returned in the pMedium structure. Image format and default image capture properties may be specified using the 1Intent and cfFormat parameters. Returns S\_FALSE if the user cancels the selection dialog without making a device selection, S\_OK if the user makes a device selection and the data is transferred or an error value if the method fails.

Parameters:

---

1Flags	Operation flags
1Intent	Intent, default image capture properties
cfFormat	Clipboard format desired by application
pMedium	Image is returned through this medium.

---

EnumDestinationInfo

---

```
HRESULT IImageInDevMgr::EnumDestinationInfo(
    LONG          1Flags,
    IUnknown*      pDevice,
    IEnumIMAGEIN_DEST_INFO** ppIEnum);
```

---

EnumImageInDestInfo creates a standard enumerator for CImageInDestInfo objects. The enumerator itself is a CEnum-

mImageInDestInfo object that has a single interface IEnumIMAGEIN\_DEST\_INFO. Applications can use this API to obtain device destination properties from an ImageIn device. Destination applications are registered using RegisterDestinationApplication.

Parameters:

1Flags	Enumeration flags
pDevice	Device object. If null destination applications for all devices are enumerated.
ppIEnum	Enumeration interface for CEnumImageInDestInfo objects.

#### RegisterDestinationApplication

```

HRESULT ImageInDevMgr::RegisterDestinationApplication(
    LONG          1Flags,
    LONG          1Intent,
    IUnknown*     pDevice,
    BSTR          bstrEvent,
    BSTR          bstrAppName,
    BSTR          bstrCommandLine);

```

This method is called when an application wishes to register as an ImageIn destination.

Parameters:

1Flags	Registration flags.
1Intent	Intent, default image capture properties.
pDevice	Device object. If null, destination application is registered for all devices.
bstrEvent	Optional event name.
bstrAppName	Friendly name of Application. This name will be displayed to the user in UI.
bstrCommandLine	Full path to the executable for this application. Additional command line arguments may be added to this command.

#### UnregisterDestinationApplication

```

HRESTITL ImageInDevMgr::UnregisterDestinationApplication
    LONG          1Flags,
    IUnknown*     pDevice,
    BSTR          bstrAppName);

```

This method is called when an application that has registered an ImageIn destination wishes to be uninstalled or no longer known as an ImageIn destination

Parameters:

1Flags	Operation flags.
pDevice	Device object. If null, destination application is unregistered for all devices.
bstrAppName	Friendly name of Application, used to register application.

#### IEnumIMAGEIN\_DEV\_INFO Interface

The IEnumIMAGEIN\_DEV\_INFO interface is a standard OLE enumeration interface that supports per device enumeration of device information properties.

Next

```

5  HRESULT IEnumIMAGEIN_DEV_INFO::Next(
    ULONG          celt,
    IPropertyStorage** rgelt,
    ULONG          *pceltFetched);

```

Next returns an array of IPropertyStorage interfaces to CImageInDevInfo objects. Applications can use the returned of IPropertyStorage interfaces to obtain device information properties from available ImageIn devices.

Parameters:

```

15  celt      Specifies the number of elements requested.
    rgelt    Address of an array in which to return the IPropertyStorage
20  pceltFetched Address of a value that receives a count of the item
           identifiers actually returned in rgelt.

```

Skip

```

25  HRESULT IEnumIMAGEIN_DEV_INFO::Skip
    (ULONG celt);

```

Skip skips device objects in the enumeration.

Parameters:

```

30  celt Number of items to skip.
35  Reset
    HRESULT IEnumIMAGEIN_DEV_INFO::Reset
    (void);
    Reset sets the enumeration back to the first device.

```

Clone

```

40  HRESULT IEnumIMAGEIN_DEV_INFO::Clone(
    IEnumIMAGEIN_DEV_INFO **ppIEnum);

```

Clone creates another IEnumIMAGEIN\_DEV\_INFO enumeration object and returns an interface pointer to it.

Parameters:

```

45  ppIEnum Address that receives a pointer to the new enumeration
           object.

```

#### IEnumIMAGEIN\_DEST\_INFO Interface

The IEnumIMAGEIN\_DEST\_INFO interface is a standard OLE enumeration interface that supports enumeration of device destination properties.

Next

```

60  HRESULT IEnumIMAGEIN_DEST_INFO::Next(
    ULONG          celt,
    IPropertyStorage** rgelt,
    ULONG          *pceltFetched);

```

Next returns an array of IPropertyStorage interfaces to CImageInDestInfo objects. Applications can use the returned of IPropertyStorage interfaces to obtain destination information properties from available ImageIn devices.

Parameters:

celt	Specifies the number of elements requested.
rgelt	Address of an array in which to return the IPropertyStorage interfaces.
poeltFetched	Address of a value that receives a count of the item identifiers actually returned in rgelt.

Skip

**HRESULT IEnumIMAGEIN\_DEST\_INFO::Skip**  
(ULONG celt);

Skip skips destination objects in the enumeration.

Parameters:

celt Number of items to skip.

Reset

**HRESULT IEnumIMAGEIN\_DEST\_INFO::Reset**  
(void);

Reset sets the enumeration back to the first device.

Clone

**HRESULT IEnumIMAGEIN\_DEST\_INFO::Clone**  
(IEnumIMAGEIN\_DEST\_INFO \*\*ppIEnum);

Clone creates another IEnumIMAGEIN\_DEST\_INFO enumeration object and returns an interface pointer to it.

Parameters:

ppIEnum	Address that receives a pointer to the new enumeration object.
---------	--

### IPropertyStorage Interface

The IPropertyStorage interface is used to query the device information and destination properties. IPropertyStorage is a standard OLE interface and is documented in the OLE Programmers Reference. All device information properties are read only. Any attempt to modify the device information properties will result in a failure with access denied. The methods of this interface are:

**HRESULT ReadMultiple**(ULONG, const PROPSPEC, PROPVARIANT);  
**HRESULT WriteMultiple**(ULONG, const PROPSPEC, PROPVARIANT, PROPID);  
**HRESULT DeleteMultiple**(ULONG, const PROPSPEC);  
**HRESULT ReadPropertyNames**(ULONG, const PROPID, LPOLESTR);  
**HRESULT WritePropertyNames**(ULONG, const PROPID, LPOLESTR);  
**HRESULT DeletePropertyNames**(ULONG, const PROPID);  
**HRESULT Commit**(DWORD);  
**HRESULT Revert**(void);  
**HRESULT Enum**(IEnumSTATPROPSTG\*\*);  
**HRESULT Set Times**(FILETIME const \*, FILETIME const \*, FILETIME const \*);  
**HRESULT SetClass**(REFCLSID);  
**HRESULT Stat**(STATPROPSETSTG \*);

### Device Information Properties

All ImageIn devices support the following basic device information properties:

Device CLSID	The CLSID of the ImageIn server for this device.
Unique Device ID	A device ID which is unique per physical device.
Vendor Description	The device manufactures name.
Device Description	A description of the device.
Device Type	A device type constant: scanner, camera . . .
Device Port Name	Name of the port through which the device is connected.
Device Friendly Name	A user readable device name.
Device Icon Resource	Resource file name and ID.
Device Bitmap Resource	Resource file name and ID.
Server Name	The name of the server where the ImageIn server for this device is running.

### ImageIn Scanner Device Object

ImageIn device objects support interfaces for querying and setting device properties, displaying device UI and transferring data. ImageIn devices are required to support a small number of standard interfaces that allow applications to deal with all devices in a common manner and transfer data from the devices in a manner that is native to the (COM) application. Device objects may also support more specialized interfaces to implement custom functions. Since the application has a direct connection to the device object, this architecture does not place any strict limits on the interfaces a device object can export. Practically speaking though, applications must know about an interface for it to be useful.

### IScan Interface

ScanDlg

<b>HRESULT</b>	<b>ScanDlg</b> ( LONG LONG	<b>IFlags,</b> <b>IIntent);</b>
----------------	----------------------------------	------------------------------------

ScanDlg presents the system or device UI needed to prepare a device for scanning. If the dialog successfully completes, the scan object will be ready to begin data transfer via the IDataObject or IImageTransfer interfaces. The default image capture properties may be specified using the optional IIntent parameter. Returns S\_FALSE if the user cancels the selection dialog without making a device selection, S\_OK if the user makes a device selection or an error value if the method fails.

Parameters:

<b>IFlags</b>	<b>Operation flags</b>
<b>IIntent</b>	<b>Intent, default image capture properties</b>

### IPropertyStorage Interface

The standard IPropertyStorage interface is used to query and set all scan device properties. IPropertyStorage is a standard OLE interface and is documented in the OLE Programmers Reference. The methods of this interface are:

**HRESULT ReadMultiple**(ULONG, const PROPSPEC, PROPVARIANT);  
**HRESULT WriteMultiple**(ULONG, const PROPSPEC, PROPVARIANT, PROPID);  
**HRESULT DeleteMultiple**(ULONG, const PROPSPEC);

-continued

HRESULT	ReadPropertyNames(ULONG, const PROPID,
LPOLESTR);	
HRESULT	WritePropertyNames(ULONG, const PROPID,
LPOLESTR);	
HRESULT	DeletePropertyNames(ULONG, const PROPID);
HRESULT	Commit(DWORD);
HRESULT	Revert(void);
HRESULT	Enum(IEnumSTATPROPSTG**);
HRESULT	SetTimes(FILETIME const *, FILETIME const *,
FILETIME const *);	
HRESULT	SetClass(REFCLSID);
HRESULT	Stat(STATPROPSETSTG *);

All ImageIn scanner devices support the following basic device properties:

Horizontal Resolution	The horizontal resolution in DPI.
Vertical Resolution	The vertical resolution in DPI.
Horizontal Scan Start Position	The horizontal start position in pixels.
Vertical Scan Start Position	The vertical start position in pixels.
Horizontal Scan Extent	The width of the scan in pixels.
Vertical Scan Extent	The height of the scan in pixels.
Scan Data Type	A data format specification constant.
Scan Color Depth	The number of bits per pixel used to specify color.

ImageIn scan devices may support additional device properties depending on hardware configuration.

#### IDevPropStream Interface

The IDevPropStream interface is used to query/set all current device properties from/to a named, non-volatile, registry based storage. The methods of this interface are:

##### ReadDevPropStream

HRESULT ReadDevPropStream(BSTR bstrName);

ReadDevPropStream reads a device property stream from the specified value and initializes the device with these properties. The properties are per user and per device.

Parameters:

bstrName Name of the property stream.

##### WriteDevPropStream

HRESULT WriteDevPropStream(BSTR bstrName);

WriteDevPropStream writes the current device property stream to the specified value. The properties are per user and per device.

Parameters:

bstrName Name of the property stream.

##### ListDevPropStreams

HRESULT ListDevPropStreams(BSTR \*pbstrName);

ListDevPropStreams lists the device property stream names present in non-volatile storage. The list is returned in an allocated BSTR which the application must free using SysFreeString.

Parameters:

pbstrName Pointer to receive a list property streams.

##### DeleteDevPropStream

HRESULT DeleteDevPropStream(BSTR bstrName);

DeleteDevPropStream deletes a device property stream from non-volatile storage.

Parameters:

Is bstrName Name of the property stream.

#### IDataObject Interface

The IDataObject interface is a standard OLE data transfer mechanism. This interface is used to provide an easy and natural way for applications to transfer data from a scan device. The full IDataObject interface description can be

found in the OLE2 Programmer's Reference. The methods of this interface are:

5	HRESULT	GetData(LPFORMATETC, LPSTGMEDIUM);
	HRESULT	GetDataHere(LPFORMATETC, LPSTGMEDIUM);
	HRESULT	QueryGetData(LPFORMATETC);
	HRESULT	GetCanonicalFormatEtc(LPFORMATETC,
	LPFORMATETC);	
10	HRESULT	SetData(LPFORMATETC, STGMEDIUM FAR *, BOOL);
	HRESULT	EnumFormatEtc(DWORD, LPENUMFORMATETC
	FAR *);	
	HRESULT	DAdvise(FORMATETC FAR *, DWORD,
	LPADVISESINK, DWORD FAR *);	
	HRESULT	DUnadvise(DWORD);
15	HRESULT	EnumDAdvise(LPENUMSTATDATA FAR *);

#### ImageTransfer Interface

The ImageTransfer is a high performance data transfer interface. This interface uses a shared memory window to transfer data from the device object to the application, eliminating unnecessary data copies during marshalling. For Simplicity, this interface uses the same format negotiation method as IDataObject. ImageTransfer uses two different mechanisms to transfer data.:

##### Banded Transfers

The device breaks a large image transfer Up into smaller transfers, which are performed sequentially into an application-specified buffer.

##### Data Callback

The device does a single large transfer, while calling back to the application as the transfer progresses.

##### itAllocateTransferBuffer

35	HRESULT	itAllocateTransferBuffer(
	LONG	IFlags,
	LONG	ISize,
	ULONG	hSection,
40	ULONG	ProcessID);

Allocates a buffer to use for scanning data from the device. The buffer is mapped into the address space of both the client and server process.

Parameters:

45	IFlags	Operation flags.
	ISize	Size in bytes of the requested buffer.
	hSection	Mapped section handle
	ProcessID	Caller process ID

##### itFreeTransferBuffer

55  
HRESULT itFreeTransferBuffer(void);  
Free the buffer created by itAllocateTransferBuffer. This buffer is also freed when the device object is destroyed.

##### itBeginTransfer

60	HRESULT	itBeginTransfer(
	LPFORMATETC	pFormatEtc,
	LONG	IFlags,
65	IDataCallback*	pIDataCallback);



Reset a device object context to begin an ImageTransfer.  
Parameters:

pFormatEtc	Format specification.
IFlags	Operation flags.
pfDataCallback	Optional transfer progress notification entry point.

ItGetImage

HRESULT	itGetImage( LONG LONG* LONG*	IFlags, pISrcOffset, pcbWritten);
---------	---------------------------------------	---

Perform an image transfer.

Parameters:

IFlags	Operation flags.
pISrcOffset	Source pointer for transfer.
pcbWritten	Actual number of bytes written during transfer.

itGetImageCB

HRESULT itGetImageCB(LONG IFlags);

Perform an image transfer using a user specified callback.

Parameters:

IFlags Operation flags.

itEndTransfer

HRESULT itEndTransfer(LONG IFlags);

Cleanup a device object context after an image transfer.

Parameters:

IFlags Operation flags.

itQueryGetData

HRESULT itQueryGetData(LPFORMATETC pfe);

Check to see if a device supports a given format in an image transfer.

Parameters:

pfe Pointer to the FORMATETC structure defining the format, medium, and target device to use for the query.

HRESULT	itEnumFormatEtc( DWORD LPENUMFORMATETC*	dw, lpEnum);
---------	---	-----------------

Create a format enumerator.

Parameters:

dw	Reserved
lpEnum	Indirect pointer to the IEnumFORMATETC interface on the new enumerator object.

ImageIn Camera Device Object

The ImageIn Camera is a hierarchical object. The top-level camera object is used to get basic device information and also to get access to individual images or image folders. The CCameraItem object represents images and image folders.

Camera Interface

TakePicture

HRESULT TakePicture();

The TakePicture method instructs a camera to take a new picture.

GetCameraRootItem

HRESULT GetCameraRootItem(ICameraItem\*\* pICameraItem);

This method returns an interface to the root CCameraItem object. Using the ICameraItem interface it is possible to enumerate all images on the camera.

Parameters:

pICameraItem Interface pointer to root camera item

15 GetCameraItemByHandle

HRESULT	GetCameraItemByHandle( ULONG ICameraItem**	ulItemHandle, pICameraItem);
---------	--	---------------------------------

This method returns an ICameraItem interface to the specified CCameraItem object. A handle for a CCameraItem object can only be obtained through the ICameraItem interface.

Parameters:

ulItemHandle	Handle to camera item, previously returned by CameraItem interface
pICameraItem	Interface pointer to Camera Item specified by handle

CameraDlg

HRESULT	CameraDlg( LONG LONG ICameraItem**	IFlags, IIntent, pICameraItem);
---------	---	---------------------------------------

Display the camera UI. UI will select an image on a device and prepare for image transfer. The UI returns a ICameraItem interface to a CCameraItem ready for data transfer. IDataObject or ImageTransfer interfaces are then used to transfer image data.

Parameters:

IFlags	Operational flags
IIntent	High level intent
pICameraItem	Interface pointer to Camera Item selected by Dlg

ICameraItem Interface

A CCameraItem object is created for every image and directory on the camera. This is done to support full and flexible hierarchical image storage on cameras. A ICameraItem pointer is returned for each CCameraItem object. ICameraItem methods are defined below.

GetItemType

HRESULT GetItemType(ULONG \*pItemType);

GetItemType returns the type of camera item the object represents. The two types of camera items are:

1. ItemTypeFolder—CCameraItem is a folder that may contain other CCameraItems

2. ItemTypeImage—CCameraItem is an image.

Parameters:

pItemType Item Type returned

GetItemHandle

HRESULT GetItemHandle(ULONG pItemHandle);

Returns a handle to the CCameraItem. This handle can later be used by the ICamera interface to get an interface pointer back to this object.

Parameters:

PItemHandle Item handle returned. This handle may be used by the GetCameraItemByHandle method of the ICamera interface to obtain an ICameraItem pointer.

OpenImagePropertyStorage

---

HRESULT OpenImagePropertyStorage(IPropertyStorage\*\* ppIPropertyStorage);

---

Returns an IPropertyStorage interface to the CCameraItem object.

Parameters:

ppIPropertyStorage Returned IPropertyStorage interface pointer.

EnumChildItems

RESULT EnumChildItems(IEnumCameraItem\*\* ppIEnumCameraItem);

Creates a CEnumCameraItem object and returns a IEnumCameraItem interface to it. This method only works if the camera item is a folder and the folder is not empty, as shown in the figure above.

Parameters:

ppIEnumCameraItem Pointer to IEnumCameraItem interface.

IEnumCameraItem Interface

IEnumCameraItem is a standard OLE enumerator interface with the usual four methods Next, Skip, Clone and Reset. This enumerator will return an ICameraInterface for each camera item in the current camera folder (that was used in the call to EnumChildItems).

Next

---

HRESULT	Next(	
	ULONG	
	ICameraItem**	celt,
	ULONG*	ppICameraItem,
		pceltFetched);

---

Return an ICameraItem interface for each CCameraItem contained by the current folder.

Parameters:

---

celt	number of camera items to get
ppICameraItem	List of ICameraItem interface pointers returned.
pceltFetched	Number of interface pointers returned

---

Skip

HRESULT Skip(ULONG celt);

Skip celt CCameraItem objects.

Parameters:

celt Number of CCameraItem objects to skip

Reset

HRESULT Reset(void);

Begin at the first CCameraItem object.

Parameters: None

5 Clone

HRESULT Clone(IEnumCameraItem \*\*ppIEnumCameraItem);

Create a new CEnumCameraItem object and return a IEnumCameraItem interface.

10 Parameters:

---

ppIEnumCameraItem	New enumerator created to exactly match this one.
-------------------	---

---

15

Camera Download Manager

The camera download manager monitors the connection status of camera devices. When a camera device is connected to the system, the Download Manager will attempt to immediately download all the images from the camera onto the system hard disk. The camera download manager will also maintain a data base of all images previously downloaded from a given camera and not download images that are already cached.

Caching images in this manner has several advantages.

Camera image download can be very slow, this cache prevents any image from needing to be downloaded more than once.

Applications do not need a special API to acquire images from a camera, simply wait for the download to complete and load the image from the file system.

Images are safely and automatically copied to the file system where they can easily be edited, archived, printed or just saved.

In order for the camera download manager to work effectively, camera events must be detectable. For example, it should be easy to detect when a camera is connected or disconnected from the system. This should be detectable without loading the entire camera driver. Also any activity performed directly on the camera (through camera controls) must be reported to software so an accurate internal model of the state of the camera can be kept.

45

Sample Code

Get an image from an ImageIn device. Use the ImageIn device manager device selection UI and the device image acquisition UI.

50

---

```

/.....
*
55 * GetImageFromImageIn
*
* DESCRIPTION:
* Use the ImageIn device manager to select a device and acquire an
* image using the device UI.
*
* PARAMETERS:
* pszDIBFileName - Name of the DIB file which contain the image data.
*...../
HRESULT GetImageFromImageIn(LPOLESTR pszDIBFileName)
{
65     HRESULT hr;
    ImageInDevMgr *pImageInDevMgr;
    // Get ImageIn device manager object.

```

21

-continued

```

hr = CoCreateInstance(CLSID_ImageInDevMgr,
    NULL,
    CLSCTX_LOCAL_SERVER,
    IID_ImageInDevMgr,
    (void**)&pImageInDevMgr);
if (SUCCEEDED(hr)) {
    STGMEDIUM StdMedium;
    // Fill in the storage medium spec and get the image.
    StgMedium.tymed = TYMED_File;
    StgMedium.lpszFileName = pszDIBfileName;
    StgMedium.pUnkForRelease = NULL;

```

22

-continued

```

hr = pImageInDevMgr->GetImage(0,
    0,
    CF_DIB,
    &StgMedium);
pImageInDevMgr->Release();
}
return hr;
}

```

Enumerate all installed ImageIn devices and get the device ID of a specific device:

```

/*****
 *
 * GetDeviceIDfromDescription
 *
 * DESCRIPTION:
 *   Get the unique device ID of an ImageIn device based on it's description.
 *
 * PARAMETERS:
 *   pszDescription - Requested device description, from device info properties.
 *   pszDeviceID - Buffer for the returned device ID.
 *   cbDeviceIDSize - Size of the returned device ID buffer in bytes.
 *****/
HRESULT GetDeviceIDfromDescription(
    LPOLESTR pszDescription,
    LPOLESTR pszDeviceID,
    UINT cchDeviceID)
{
    HRESULT hr;
    ImageInDevMgr *pImageInDevMgr;
    if (pszDeviceID && cchDeviceID) {
        *pszDeviceID = '\0';
    }
    else {
        return E_INVALIDARG;
    }
    // Get ImageIn device manager object.
    hr = CoCreateInstance(CLSID_ImageInDevMgr,
        NULL,
        CLSCTX_LOCAL_SERVER,
        IID_ImageInDevMgr,
        (void**)&pImageInDevMgr);
    if (SUCCEEDED(hr)) {
        IEnumIMAGEIN_DEV_INFO *pEnumIMAGEIN_DEV_INFO;
        PROPSPEC PropSpec[1];
        PROPVARIANT PropVarDesc[1], PropVarID[1];
        UINT cbSize;
        // Get an enumerator for the ImageIn device information.
        hr = pImageInDevMgr->EnumImageInDevInfo(0, &pEnumIMAGEIN_DEV_INFO);
        if (SUCCEEDED(hr)) {
            IPropertyStorage *pPropStg;
            ULONG ul;
            // Enumerate the ImageIn devices, getting a ImageInDevInfo
            // pointer for each. Use this interface to query the registry
            // based properties for each installed device.
            ul = 1;
            while ((hr = pEnumIMAGEIN_DEV_INFO->Next(1,
                &pPropStg,
                &ul)) == S_OK) {
                // Read the device description for the current device.
                PropSpec[0].ulKind = PRSPEC_PROPID;
                PropSpec[0].propid = DIP_DEV_DESC;
                hr = pPropStg->ReadMultiple(1, PropSpec, PropVarDesc);
                if (SUCCEEDED(hr)) {
                    // Test for a description match.
                    if (lstrcmp(PropVarDesc[0].pwszVal, pszDescription)) {
                        // Read the device ID.
                        PropSpec[0].propid = DIP_DEV_ID;
                        hr = pPropStg->ReadMultiple(1, PropSpec, PropVarID);
                        if (SUCCEEDED(hr)) {

```

-continued

```

        wcsncpy(pszDeviceID, PropVarID[0].pwszVal, cchDeviceID);
        PropVariantClear(PropVarID);
    }
    PropVariantClear(PropVarDesc);
}
pIPropStg->Release();
if (*pszDeviceID) {
    break;
}
}
pIEnumIMAGEIN_DEV_INFO->Release();
}
pIImageInDevMgr->Release();
if (!*pszDeviceID) {
    hr = E_FAIL;
}
}
return hr;
}

```

Although the invention has been described in language specific to structural features and/or methodological steps, it is to be understood that the invention defined in the appended claims is not necessarily limited to the specific features or steps described. Rather, the specific features and steps are disclosed as preferred forms of implementing the claimed invention.

What is claimed is:

1. An image acquisition system comprising:  
a computer having a memory;  
an imaging device coupled to the computer, the imaging device having a device memory, the imaging device capturing a digital image and storing the image on one of the computer memory or the device memory;  
an image device manager executable on the computer to control operation of the imaging device; and  
a user interface with a menu and toolbar area, a context space separate from the menu and tool bar area, and a persistently-visible imaging menu positioned within the context space, the imaging menu listing options that are particular to controlling the imaging device and managing images captured by the imaging device.
2. An image acquisition system as recited in claim 1, wherein the imaging menu includes a capture option that directs the imaging device to capture an image and to store the image in the memory of the computer.
3. An image acquisition system as recited in claim 1, wherein the context space lists image files stored on at least one of the device memory or the computer memory.
4. An image acquisition system as recited in claim 1, wherein:  
the imaging device is a scanner; and  
the context space presented by the user interface contains a preview scan area that shows a preview of an image in the scanner.
5. An image acquisition system as recited in claim 1, wherein  
the imaging device is a scanner; and  
the context space presented by the user interface contains a scan area that is initially empty prior to a time when the scanner scans an image and then progressively displays the image as the scanner scans the image.
6. An image acquisition system as recited in claim 1, wherein the context space exhibits a play-in-place video file at a location, the play-in-place video file being actuatable to play a video stream at the location in the context space.

7. An image acquisition system as recited in claim 1, further comprising an operating system stored in the memory and executable on the computer, the image device manager being incorporated into the operating system.

8. An image acquisition system as recited in claim 1, further comprising a browser stored in the memory and executable on the computer, the image device manager being incorporated into the browser.

9. In an image acquisition system having a computer and an imaging device coupled to the computer, an image manager implemented in software stored in the computer comprising:

a user interface with a menu and toolbar area, the user interface presenting a context space of an imaging context and a persistently-visible imaging menu positioned within the context space, the context space being separate from the menu and toolbar area, the imaging menu listing options that are particular to operating the imaging device and managing image files; and

an image device driver to control operation of the imaging device in response to selected options in the imaging menu.

10. An image manager as recited in claim 9, wherein the imaging menu includes a capture option to capture an image from the imaging device, and the image device driver directs the imaging device to capture the image into an image file for storage on the imaging device or the computer in response to selection of the capture option.

11. An image manager as recited in claim 9, wherein the context space holds image files and the imaging menu includes an option to operate on one or more of the image files.

12. An image manager as recited in claim 9, wherein the context space exhibits a play-in-place video file at a location, the play-in-place video file being actuatable to play a video stream at the location in the context space.

13. An image manager as recited in claim 9, wherein the imaging device coupled to the computer is a scanner and the context space of the user interface pertains to a scanner context and contains an area that is initially empty prior to a time when the scanner scans an image and then progressively displays the image as the scanner scans the image.

14. An operating system embodied on a computer readable medium comprising an image manager as recited in claim 9.

15. A file system embodied on a computer readable medium comprising an image manager as recited in claim 9.

25

16. A browser program embodied on a computer readable medium comprising an image manager as recited in claim 9.

17. A user interface embodied on a computer-readable medium and executable on a computer comprising:

a menu and toolbar area;

a file space of a selectable context, the file space being separate from the menu and toolbar area and exhibiting one or more files and/or folders pertaining to the context; and

a persistently-visible context-specific menu positioned within the file space adjacent to the files and/or folders, the context-specific menu listing options that are particular to the context of the file space.

18. A user interface as recited in claim 17, wherein the files comprise digital image files and the folders comprise sets of digital image files.

19. A user interface as recited in claim 17, wherein the context of the file space pertains to imaging devices, and the options listed in the context-specific menu include a command to capture digital images using an imaging device coupled to the computer.

20. A user interface as recited in claim 17, wherein the file space also exhibits a play-in-place video file at a location, the play-in-place video file being actuatable to play a video stream at the location in the file space.

21. A user interface as recited in claim 17, wherein the options in the context-specific menu change in response to changing the context of the file space.

22. A file system embodied on a computer-readable medium incorporating the user interface as recited in claim 17.

23. An operating system embodied on a computer-readable medium incorporating the user interface as recited in claim 17.

24. A browser embodied on a computer-readable medium incorporating the user interface as recited in claim 17.

25. A computer-implemented method for execution in a graphical user interface windowing environment, comprising:

presenting a graphical window with a menu and toolbar area;

presenting a set of one or more files and/or folders in a file space within the graphical window and separate from the menu and toolbar area;

presenting a persistently-visible, context-specific menu within the file space adjacent to the files and/or folders; and

listing options in the context-specific menu that are particular to operating on the files and/or folders in the file space.

26. A computer-implemented method as recited in claim 25 wherein the presenting comprises presenting a set of digital image files.

27. A computer-implemented method as recited in claim 25 further comprising operating on the files and/or folders in response to selection of an option in the context-specific menu.

28. A computer-implemented method as recited in claim 25 further comprising exhibiting a play-in-place video file at a location in the file space, the play-in-place video file being actuatable to play a video stream at the location in the file space.

29. A computer-implemented method as recited in claim 25 further comprising:

presenting a new set of one or more files and/or folders in the file space; and

26

listing new options in the context-specific menu that are particular to operating on the new set of files and/or folders.

30. An image manager comprising:

first and second image device drivers to control operation of respective first and second imaging devices;

a user interface presenting a menu and toolbar area and a context space separate from the menu and toolbar area, the context space being adaptable to relate to a first context associated with the first imaging device and to relate to a second context associated with the second imaging device image;

the user interface further presenting a persistently-visible imaging menu positioned within the context space to list options particular to operating the first imaging device when the first context is presented and to list options particular to operating the second imaging device when the second context is presented; and

the first and second image device drivers being configured to control operation of the first and second imaging devices, respectively, in response to selected options in the imaging menu.

31. An image manager as recited in claim 30, wherein the first imaging device is a scanner and the second imaging device is a camera.

32. An image manager as recited in claim 30, wherein the first imaging device is a scanner and the first context pertains to a scanning context, the imaging menu being configured to include a capture option to capture an image from the scanner.

33. An image manager as recited in claim 30, wherein the first imaging device is a scanner and the first context pertains to a scanning context that defines an area that is initially empty prior to a time when the scanner scans an image and then progressively displays the image as the scanner scans the image.

34. An image manager as recited in claim 30, wherein the context space holds files and/or folders and the imaging menu includes an option to operate on one or more of the image files and/or folders.

35. An image manager as recited in claim 30, wherein the context space exhibits a play-in-place video file at a location, the play-in-place video file being actuatable to play a video stream at the location in the context space.

36. An operating system embodied on a computer readable medium comprising an image manager as recited in claim 30.

37. A file system embodied on a computer readable medium comprising an image manager as recited in claim 30.

38. A browser program embodied on a computer readable medium comprising an image manager as recited in claim 30.

39. A user interface embodied on a computer-readable medium and executable on a computer comprising:

a menu and toolbar area;

a file space of a selectable context, the file space being separate from the menu and toolbar area and exhibiting one or more files and/or folders pertaining to the context; and

a persistently-visible context-specific menu positioned within the file space adjacent to the files and/or folders, the context-specific menu listing options that are particular to the context of the file space so that upon selection of a first context, the file space is populated with one or more files and/or folders pertaining to the

27

first context and the persistently-visible context-specific menu lists options pertaining to the first context and upon selection of a second context, the file space is populated with one or more files and/or folders pertaining to the second context and the persistently-visible context-specific menu list options pertaining to the second context.

40. A user interface as recited in claim 39, wherein the files comprise digital image files and the folders comprise sets of digital image files.

41. A user interface as recited in claim 39, wherein the first and second contexts of the file space pertain to different imaging devices, and the options listed in the context-specific menu include a command to capture digital images using one or more imaging devices coupled to the computer.

28

42. A user interface as recited in claim 39, wherein the file space also exhibits a play-in-place video file at a location, the play-in-place video file being actuatable to play a video stream at the location in the file space.

43. A file system embodied on a computer-readable medium incorporating the user interface as recited in claim 39.

44. An operating system embodied on a computer-readable medium incorporating the user interface as recited in claim 39.

45. A browser embodied on a computer-readable medium incorporating the user interface as recited in claim 39.

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 6,373,507 B1  
DATED : April 16, 2002  
INVENTOR(S) : Camara et al.

Page 1 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 2,

Line 4, add -- so -- after "and".

Line 55, delete "Is" after "general-purpose".

Column 4,

Line 1, replace "UT" with -- UI --.

Column 6,

Table 1, column 1, add -- View Properties -- under "Rotate to the Left".

Table 1, column 2, for the option "View Properties" add -- Allows the user to view properties associated with the selected picture(s) --.

Table 1, column 2, for the option "Rotate to the Left" replace "Allows the user to view properties associated with the selected picture(s)" with -- Allows the user to rotate the picture 90 degrees to the left --.

Line 47, add -- camera tab 160 -- after "the".

Column 7,

Line 47, replace "4stop" with -- stop --.

Column 15,

Line 62, delete "Is" before "bstrName".

Column 16,

Line 26, replace "Up" with -- up --.

Column 18,

Line 24, delete "D" after "obtained".

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 6,373,507 B1  
DATED : April 16, 2002  
INVENTOR(S) : Camara et al.

Page 2 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:


Column 21,

Line 10, replace "StdMedium" with -- StgMedium --.

Signed and Sealed this

Tenth Day of September, 2002

Attest:

A handwritten signature in black ink, appearing to read "James E. Rogan", with a horizontal line drawn underneath it.

Attesting Officer

JAMES E. ROGAN  
*Director of the United States Patent and Trademark Office*